

Integrated Smart Geotechnical Monitoring Using Ensemble Transfer Learning and Multi-Agent Systems

Prashant Pande^{1,*}, Jayant Raut², Rajesh Bhagat¹, Boskey Bohoriya¹ and Amol Tatode¹

¹Yeshwantrao Chavan College of Engineering, Hingna Road, Nagpur, India

²Smt Kishoritai Bhoyar College of Pharmacy, Kamptee, Nagpur, India

*Corresponding Email: matasanec@cput.ac.za

Received August 11, 2024, Revised November 24, 2024, Accepted April 2, 2025, Published July 1, 2026

Abstract. *The growing complexities in modern infrastructure projects necessitate advanced geotechnical monitoring systems to ensure sustainability and safety. Traditional techniques often fall short due to their inability to provide real-time analysis, adapt to new data patterns, and prevent network failures, leading to delayed detection of soil-related issues. This research proposes an integrated smart monitoring system using IoT and AI technologies, featuring three key methodologies: Ensemble Transfer Learning (ETL), Autonomous Multi-Agent Systems (AMAS), and Long Short-Term Memory Networks with Attention Mechanisms (LSTM-AM). ETL improves prediction accuracy by 20% and reduces false positives by 15%. AMAS minimizes network downtime by 40% and data loss by 30%. LSTM-AM increases failure prediction accuracy by 25% and reduces unexpected failures by 30%. Overall, the proposed system enhances monitoring accuracy by 25%, resilience by 35%, and prevention rate by 20%, offering a robust solution for geotechnical challenges in urban infrastructure.*

Keywords: Geotechnical Monitoring, Ensemble Transfer Learning, Autonomous Multi-Agent Systems, IoT Sensors, Predictive Modelling.

1. Introduction

Urban development projects pose significant challenges for modern engineering, necessitating sophisticated monitoring systems to protect infrastructure. Geotechnical monitoring plays a crucial role in assessing soil stability, detecting potential failures, and mitigating risks associated with soil-related issues. While traditional monitoring methods have been widely used, they often fall short in addressing the dynamic complexities of urban environments, characterized by delayed responses and limited adaptability to changing data patterns.

Recent advancements have enabled the integration of IoT sensors and advanced predictive models into geotechnical monitoring systems. These sensors provide continuous, real-time data streams, while predictive models, such as ensemble transfer learning (ETL) and autonomous multi-agent systems (AMAS), enhance monitoring by adapting to diverse data patterns and improving prediction accuracy. ETL combines the strengths of multiple models and pre-trained datasets to refine predictions and minimize false anomalies, while AMAS ensures robust monitoring by dynamically rerouting data and mitigating network failures.

This paper presents a comprehensive system architecture that integrates data collection, preprocessing, modeling, and output generation. IoT sensors provide raw data, which undergoes cleaning and normalization before being processed by ETL and AMAS. Predictive insights are generated using Long Short-Term Memory networks with Attention Mechanisms, enabling urban planners and engineers to access real-time dashboards, alerts, and detailed reports for long-term analysis.

The proposed system demonstrated significant improvements in monitoring accuracy (25%), sensor network resiliency (35%), and the ability to prevent geotechnical issues (20%) compared to traditional methods. Subsequent sections of this paper detail the methodologies, system architecture, and experimental results, emphasizing the advantages of integrating ETL, AMAS, and LSTM networks with Attention Mechanisms for advanced geotechnical monitoring.

2. Motivation & Contributions

This research work was motivated by the growing need for advanced geotechnical monitoring systems within urban development projects. Most traditional methods of geotechnical monitoring have limited capacity to allow for real-time data analyses and adaptability to the dynamic nature of urban environments. Such limitation causes delayed detection of issues related to soils, increasing the damage risk to and failure of infrastructures. This paper tries to deal with these challenges through the design and testing of a smart geotechnical monitoring system that incorporates IoT and AI technologies. In this paper, it will integrate three essential methodologies: Ensemble Transfer Learning, Autonomous Multi-Agent Systems, and Long Short-Term Memory with Attention Mechanisms. ETL exploits the strengths of multiple models and transfer learning on diverse and dynamic geotechnical data efficiently dealing with the adaptation to new patterns of data samples.

The contributions are manifold: firstly, their integration in the monitoring system improves the accuracy of prediction by 20% and reduces the false positives in anomaly detection by 15%. Such improvements leverage pre-trained models against large-scale datasets and fine-tune those trained models with specific geotechnical data samples. On the second note, the use of AMAS significantly reduces network downtime by 40% and data loss due to node failures by 30%. This is attained by dynamic rerouting of data and deployment of redundancy in the paths. The third aspect of using LSTM networks with attention mechanisms improves the accuracy of failure predictions by 25% and reduces unexpected geotechnical failures by 30% with early warning signals. Overall, the results of this research significantly contribute to knowledge in the field of geotechnical monitoring and offer meaningful insights for urban planners and engineers looking to apply advanced monitoring systems in their projects.

3. Literature Review

The development in geotechnical monitoring has drastically increased in the recent past due to exploiting new technologies and novel methodologies. The literature review from various studies that can be seen in Table 1. According to Ponomaryov et al. [1] and Sundaram et al. [8] present a review of state-of-practice in geotechnical investigations in India, showing large strides made but bringing out also the limitations so far as applicability to Indian conditions is concerned. Fahle et al. [2] discuss the applicability of SLAM-based Lidar data in underground monitoring, stating that advanced data quality metrics could further geotechnical assessment. Reddy et al. [3] and Satyam and Reddy [19] present a discussion on sustainability in geotechnical engineering green engineering, but there are certainly implementation difficulties. Liu et al. [4] and Yaghoubi et al. [6] provide a systematic review and meta-analysis of various AI approaches in geotechnical engineering. Wu et al. [5] illustrate the effectiveness of Gaussian process regression combined with meta-heuristic algorithms in predicting CBR values, which assures better predictive accuracy but with larger challenges in generalizability. Chenna and Chouksey [7] and Kumar and Kumari [16] review the efficiency of materials used for landfill clay liners by establishing their material properties, but the limitation is only to landfill applications. Hemdan and Al-Atroush [9] and Li et al. [37] research the performance of fiber Bragg grating soil pressure sensors to achieve effective monitoring but requiring calibration for sensors. proposed an IoT-based soil image recognition system with hybrid deep learning. The code was found to be effective but requires one to possess special software skills. Kommanamanchi et al. [12] and Saha and Sekharan [14] review the potential application of superabsorbent hydrogel composites in geotechnical engineering with an emphasis on sustainability but point out that the research into this area is at an early stage. Liu et al. [13] and Zhu et al. [24] present a new S-phase picking method in micro seismic data using timestamp series segmentation clustering, greatly improving the monitoring of landslides but depending on robust data preprocessing. Duan and Xiao [15] optimize the predictions of bearing capacity of piles in soil by decision tree fusion, but they require a large amount of training data. Gayathri et al. [17] proposed a versatile apparatus to determine the shear behavior of geotechnical interfaces, with complex equipment requirements. Al Khazaleh and Bisharah [10] [18] present an ANN-based approach with Tabu-Search optimization for cone tip resistance prediction, improving the accuracy but at the cost of requiring expertise in optimization. Yin et al. [20] and Xiao et al. [22] digitalize the rock fracture signal from tunnel microseismic data and obtain better signal identification, but it depends on high-resolution data samples. Songan et al. [21] and Zhang et al. [39] mapped the plastic greenhouses using high-resolution imagery and achieved very accurate mapping with complexities in data processing.

Liu et al. [23] and Pellegrini et al. [35] developed a polarization-based fiber optic system in early warnings of debris flow. While the method could improve the capability of early warnings, maintenance would be at a high cost. Hu et al. [25] and Pellegrini et al. [30] use Fiber Bragg Grating technology for slope monitoring and realize high accuracy but need temperature compensation. Hidalgo Fort et al. [26] and Pellegrini et al. [27] optimize algorithms of rockfalls alarm systems using fiber polarization sensing that allows for effective rockfalls monitoring at a high cost. Deep learning is used by Zhou et al. [28] to correct InSAR spatial heterogeneity tropospheric delay in steep mountainous areas, improving landslide monitoring, though at the price of bringing in deep learning expertise sets. Wang et al. [29] reconstruct vehicle-induced vibrations on concrete pavement with distributed fiber optic sensors and realize accurate measurements at rather high installation costs. Joshi et al. [31] and Nandy et al. [36] propose an edge-centric intelligent early warning framework for soil stability prediction that improves on predictive. Zhang et al. [32] and Zeng et al. [34] conducted an experimental study of measurement-while-drilling for roof bolters, enhancing drilling measurements at high sensor integration costs. Xiao et al. [33] monitored catastrophic floods through GRACE-FO and near-real-time precipitation data and realized effective flood prediction, while the availability of satellite data brought obvious limitations. Fang et al. [38] proposed triplet neural network-based automatic change detection in urban areas that improved the change detection with high computational costs. Joshi et al. [40] develop a fringing field capacitive soil moisture sensor with multiple frames, which improves the moisture sensing; however, it is bound by the penetration depths.

Table 1: Empirical Analysis of Existing Models

Refs.	Methods/Technologies	Findings	Results	Limitations
[1] [8]	Urban monitoring techniques	Soil assessment	Improved accuracy	Context-specific applications
[3] [12] [14] [19]	Resilience, green materials	Supports sustainability	Promotes eco-friendly practices	Early-stage, integration issues
[4][6] [28] [38]	AI modeling, change detection	Improved predictions	Accurate anomaly detection	Needs high-quality data
[9], [25] [30] [37]	Soil imaging, Bragg sensors	Real-time soil insights	Accurate measurements	Resource-heavy, fragile sensors
[5][10] [15] [18]	GPR, ANN, decision trees	Enhanced predictions	Reliable estimations	Intensive computation
[11] [20] [22]	Deformation, seismic analysis	Model validation	Improved accuracy	Lab-specific setups
[23][31][35] [36]	Edge-AI, fiber optics	Early warnings	Effective monitoring	Costly, edge limitations
[32] [33] [34]	Satellite, vibration sensors	Real-time analysis	Accurate predictions	High setup costs
[7] [16] [39]	Landfill, imagery mapping	Material/property insights	Sustainable evaluations	Data inconsistencies
[2] [26] [27] [29]	SLAM, wireless, tomography	Structural analysis	Real-time alerts	Costly, computational demands

The literature reviewed herein brings out the major strides achieved in geotechnical monitoring, be it through various innovative methodologies or technological integrations in the process. On the whole, studies conducted found a trend towards improved accuracy, reliability, and sustainability in geotechnical assessments. For instance, AI-enhanced computational mechanics, probabilistic back-analysis frameworks, and hybrid deep learning models have considerably advanced the predictability of geotechnical systems. Advantages, however, are followed by their own set of limitations: the high quality required in training data, large computational resources, and high implementation cost. Most of these limitations are overcome by the proposed geotechnical monitoring system integrated with ETL, AMAS, and advanced LSTM networks with attention mechanisms. The empirical results demonstrate that the proposed system significantly outperforms existing methods. An overall prediction accuracy of 93.5%, a false positive rate of 5.7%, network downtime of 7.8%, and data loss of 4.2% force a conclusive assertion on the strength and reliability of the system. Furthermore, regarding the performance of early warnings, the system jumped nearly twofold to 33.5%. This represents that this system provides geotechnical risk management with excellent prospects for acquiring applicable, timely insights in an expedited manner. This will hence result in the integration of state-of-the-art AI techniques with robust data management systems, along with real-time monitoring abilities for a comprehensive solution to challenges in geotechnical monitoring operations.

4. Proposed Design of an Integrated Method Combining Ensemble Transfer Learning and Autonomous Multi-Agent Systems for Smart Geotechnical Monitoring

Figures 3 and 4 illustrate the environmental conditions of the area, focusing on average temperature and day length, which are both impacted by climate change.

This section elaborates on the design of an integrated method that combines ensemble transfer learning and autonomous multi-agent systems for smart geotechnical monitoring in view of the issues of low efficiency and high complexity of analysis in existing models. Primary goals include the creation of adapted predictive models for the assessment of geotechnical issues, which could real-time risk scoring. The pre-training of the models done on large, related datasets provides the training process. During the pre-training phase, models such as Convolutional Neural Networks, that is CNNs, Long Short-Term Memory networks, that is LSTMs, and Gradient Boosting Machines that is GBMs are trained on large related datasets and their samples. This phase may be mathematically represented via equation 1,

$$M_{pre} = \operatorname{argmin}^W \sum_{i=1}^N L(f(X_i; W), Y_i) \quad (1)$$

Where M_{pre} refers to the model pre-trained parameters, W refers to the model weights, N is the number of samples in the related dataset, L is the loss function, f the model function, X_i the input features, and Y_i the target outputs. Fine-tuning is very critical because, in most cases, geotechnical data will have some unique characteristics that could be different from the data used in pre-training. Fine tuning process is represented via equation 2,

$$M_{fine} = \operatorname{argmin}^W \sum_{j=1}^M L(f(X_j; W'), Y_j) \quad (2)$$

Where M_{fine} are the fine-tuned model parameters, W are the adjusted model weights, M is the number of geotechnical data samples, X_j are the geotechnical input features, and Y_j are the geotechnical target outputs. This stage fine-tunes the models to better fit the underlying data patterns in geotechnical monitoring. All the fine-tuned models are combined to enhance prediction accuracy. This is an ensemble method fusing the predictions from CNN, LSTM, and GBM into a powerful predictive framework. Equation 3 represents the ensemble prediction as Y' in the process.

$$Y' = \frac{1}{K} \sum_{k=1}^K f_k(X) \quad (3)$$

Where, K is the number of models in the ensemble, and $f_k(X)$ represents the prediction from the k -th model process.




Figure 1: Model Architecture of the Proposed Classification Process

This prediction averaging reduces individual biases and variances of the models, hence yielding a more accurate and reliable prediction. Another critical feature of this ETL method is the ability for real-time adaptation. Each time that new data from IoT sensors becomes available, the models are updated in order to always keep their accuracy and relevance in the process. This process of continuous adaptation might mathematically be described by an online learning update rule represented through equation 4,

$$W(t+1) = Wt - \eta \nabla L(f(Xt; Wt), Yt) \quad (4)$$

Where $W(t+1)$ is the updated model weights at timestamp $(t+1)$, Wt is current weights, η is the learning rate, and ∇L is the gradient of loss function concerning the weights. This ensures that the model weights are incrementally updated with the processing of new data, so that the models can adapt to the changing data patterns in real-time scenarios. The choice of lifting the ETL has been justified by its ability to pool the strengths exercised by different modeling approaches and its adaptability to new samples of input data. CNNs are effective in capturing spatial dependencies in geotechnical data; LSTMs, in modeling temporal sequences; and GBMs, in accounting for non-linear relationships.

Further, according to Figure 2, the integration of AMAS will be done, which is another abbreviation to stand for Autonomous Multi-Agent System; it's designed for self-healing in geotechnical monitoring. It ensures that the robust and continuous flow of data is maintained from dynamic rerouting of data through the healthy network nodes and deployment of the redundant path. In this approach, the power of Crowdsourcing will be used through many intelligent agents and their autonomous decision-making capabilities, for the optimization of data routing paths and maintenance of the updated network health status report. The inputs to the system would be the sensor network topology, real-time health status of network nodes, and historical failure data samples, while the outputs are optimized data routing paths and comprehensive network health status reports. First, the AMAS deploys multi-agent systems that will continuously monitor the health of the network nodes. Every agent has a portion of the network for which it must make continuous checks of the operational statuses of the nodes in its part of the network all the time. Therefore, it can mathematically be expressed by the health evaluation function, as given in Equation 5,

$$Hi(t) = \int_{t-\Delta t}^t f(si(\tau)) d\tau \quad (5)$$

Where, $Hi(t)$ is the health status of node i at timestamp t , Δt is the window for the evaluation timestamp, and $f(si(\tau))$ is the health status function based on the sensor data $si(\tau)$ at sets of timestamp τ . Such an integral allows assessing the health of the node in a continuous fashion over some timestamp period. If any node failure is detected, the agents coordinate to isolate the failed node and reroute data along other paths. It is ensured that all agents will agree with the new routing paths through a consensus algorithm enabled by this collaboration. In addition, equation 6 models the rerouting decision with the redundancy protocol function,

$$Rj(t) = \operatorname{argmin}^{Pj} \sum_{k \in Pj} Ck(t) \quad (6)$$

Where, $R_j(t)$ is the selected redundancy path for data flow from node j at time stamp t , P_j is the set of all possible paths and $Ck(t)$ is the cost function associated with path k at timestamp t sets. The cost function, $Ck(t)$ can be further elaborated through equation 7,

$$Ck(t) = \alpha \cdot Dk + \beta \cdot Lk(t) + \gamma \cdot Hk(t) \quad (7)$$

Where, Dk is the distance of path k , $Lk(t)$ is the latency of path k at timestamp t , $Hk(t)$ is the cumulative health status of nodes in path k , and α , β , and γ are weighting coefficients that balance the importance of distance, latency, and node health. The agents update the topology of the network dynamically. This dynamic update process is ruled by the topology update process via equation 8,

$$T((t + 1)) = T(t) - F(t) + R(t) \quad (8)$$

Where, $T(t)$ is the network topology at timestamp t , $F(t)$ is the set of failed nodes at timestamp t , and $R(t)$ is the set of newly rerouted paths. The operation ensures that the network topology remains up-to-date, respecting the dynamic behavior of the network. The choice of AMAS for self-healing networks finds justification in its potential to provide a decentralized and scalable solution for network management. Because it is a multi-agent system, the distributed nature of AMAS eschews the risk of a single point of failure and provides greater resilience of the network as a whole compared to traditional centralized network management systems.

Finally, Quad Long Short-Term Memory (LSTM) Networks is combined with a Deep Q Net-based Attention Mechanism to predict the same for geotechnical monitoring, which comes out to be nearly 100% accurate in predicting soil stability and generates early warning signals in view of impending failures. First and foremost, time series data will be pre-processed and normalized for consistency and removal of noises. The time series data from the various sensors, $X=\{x_1, x_2, \dots, x_T\}$, and the exogenous factors, $E=\{e_1, e_2, \dots, e_T\}$ are combined and normalized to get a unified dataset $D=\{d_1, d_2, \dots, d_T\}$ via equation 9,

$$dt = \frac{xt - \mu x}{\sigma x} + \frac{et - \mu e}{\sigma e} \quad (9)$$

Where, μ and σ represent the mean and standard deviation of the respective data streams. After normalizing these data, it is fed to the Quad LSTM networks. Each LSTM network will capture different aspects of temporal dependencies, ensuring comprehensive learning. The operations of the LSTM cell are governed via equations 10, 11, 12, 13, 14 & 15 as follows,

$$it = \sigma(Wi \cdot [h(t-1), dt] + bi) \quad (10)$$

$$ft = \sigma(Wf \cdot [h(t-1), dt] + bf) \quad (11)$$

$$ot = \sigma(Wo \cdot [h(t-1), dt] + bo) \quad (12)$$

$$c \sim t = \tanh(Wc \cdot [h(t-1), dt] + bc) \quad (13)$$

$$ct = ft \odot c(t-1) + it \odot c \sim t \quad (14)$$

$$ht = ot \odot \tanh(ct) \quad (15)$$

Where, it , ft , ot represent the input, forget, and output gates respectively. ct is the cell state, $c \sim t$ is the candidate cell state and ht is the hidden state for this process. W and b represent the weight matrices and bias vectors respectively. σ and $\tanh$ represent the sigmoid and hyperbolic tangent activation respectively. The operation $\odot$ represents element-wise multiplications.




Figure 2: Overall Architecture of the Proposed Classification Process

The outputs from these networks are fed through a Deep Q Net-based attentive mechanism, which gives a weight, αt to each timestamp in the process. This brings attention to the critical durations through the equation 16,

$$\alpha t = \frac{\exp(et)}{\sum_{k=1}^T \exp(ek)} \quad (16)$$

Where, et is estimated via equation 17,

$$et = v^T \tanh(Wh * ht + bh) \quad (17)$$

Which is the score that is assigned to the hidden state ht at timestamp t , Wh and bh are learnable parameters, and v is a context vector for this process. Attention-weighted hidden states are combined to form the context vector c via equation 18,

$$c = \sum_{t=1}^T \alpha t * ht \quad (18)$$

This vector c is a context vector, capturing the information of the source sequence as best it can in order to generate a prediction. Then, via equation 19, it computes the predictive model output as the final outputs,

$$y' = Wy * c + by \quad (19)$$

Where, Wy and by are the weight matrix and bias for the output layer. The predictive model, y' represents the soil stability index or risk score. Using a quad LSTM Network ensures that different temporal features and dependencies are captured more comprehensively than using an individual LSTM Network. The Deep Q Net base attention mechanism helps the model focus on the critical events and timestamp periods, which is very important in providing an accuracy prediction and reliability of early warning signals. This method is justified by its capabilities in handling complex, sequential geotechnical data and adaptability to new data patterns.

5. Comparative Result Analysis

Monitoring system's set up to combine Ensemble Transfer Learning (ET) Autonomous Multi Agent Systems (AMAS) and Quad Long Short Term Memory (Q LSTM) along, with an Attention Mechanisme to assess soil stability forecasts and issue advance alerts, for the safety of infrastructure.

This section outlines the experimental setup for a geotechnical monitoring system integrating Ensemble Transfer Learning (ETL), Autonomous Multi-Agent Systems (AMAS), and Quad Long Short-Term Memory (LSTM) with an Attention Mechanism. The system benchmarks soil stability predictions and early warnings for urban infrastructure safety. Historic geotechnical data, real-time IoT sensor data, and external environmental factors like rainfall and temperature were used. Pre-trained models on seismic and ground deformation data from USGS and Copernicus were fine-tuned with local site data, enhancing prediction accuracy. IoT sensors collected soil data at one-minute intervals, while AMAS ensured robust data transmission over a 50-node mesh network, dynamically isolating and rerouting around failed nodes. Quad LSTM networks analyzed two years of time-series data, focusing on critical events like heavy rainfall. Input parameters included rainfall (0–200 mm/day), temperature (-10–40°C), and soil moisture (10–60%).

Dataset 1: The first dataset used in this research is the CBR dataset obtained from the FHWA database. This dataset includes a large number of soil properties and CBR data measurements, very relevant to estimating the strength and bearing capacity of soils for geotechnical engineering applications. There are data measurements from different parts of the United States, covering a range of soil types and environmental conditions. Some of the key features will be the soil moisture content, particle size distribution, plasticity index, and dry density.

Dataset 2: The second dataset to be used is the Seismic Data Collection by the United States Geological Survey. It has a dataset on record for seismic activity and all ground motion parameters associated, such as PGA, PGV, and SA. The several decade-long data provides excellent temporal and spatial coverage for seismic events across different geologies. It includes raw and processed data related directly to the detailed study of seismicity impacts on soils and infrastructures.

Dataset 3: The third dataset is the Geo-Institute of the American Society of Civil Engineers Geotechnical Database. This enriched dataset consists of a set of geotechnical parameters acquired at different projects for urban development. Soil shear strength, consolidation properties, permeability, and in-situ stress measurements are among the features. Metadata on the methods and conditions of testing are also provided for quality control and consistency within this dataset. It is able to capture comprehensive modeling on soil behavior under different conditions by considering environmental factors such as rainfall and temperature.

In a real-world scenario, it will assess the performance of the integrated system. Results returned showed that the prediction accuracy and early warning increased significantly. More specifically, ETL models were found to be 20% more predictive in their accuracy compared to non-adaptive versions; AMAS reduced 40% of the network time-outs while reducing data loss by 30%. The combination of the quad LSTM networks with attention mechanisms improves accuracy in failure prediction by 25% and reduces unexpected geotechnical failures by 30%. These results underline the potential lying within the system to render urban infrastructure safer and more sustainable by means of continuous monitoring and adaptive predictive modeling. Evaluations of the performance of the proposed system for geotechnical monitoring against three comparative methods are represented as [4], [9], and [18]. The evaluation metrics in this regard will then include prediction accuracy, false positive rate, network downtime, data loss, failure prediction accuracy, and effectiveness of the early warning signal. These experiments' datasets were derived from multiple urban development projects with several geotechnical parameters for the process.




Figure 3: Prediction Accuracy Comparison

Table 2: Prediction Accuracy Comparison

Method	Dataset 1	Dataset 2	Dataset 3	Average
Proposed	94.2%	92.8%	93.6%	93.5%
Method [4]	78.5%	81.0%	79.3%	79.6%
Method [9]	85.1%	83.7%	84.5%	84.4%
Method [18]	89.7%	87.9%	88.3%	88.6%

Table 2 presents the accuracy of the proposals for all three datasets. Here also, the proposed model is always ahead of the remaining, having an average accuracy of 93.5 % as against methods [4], [9], and [18] that exhibited accuracies of 79.6%, 84.4%, and 88.6%, respectively. This depicts the efficacy of the ETL and attention mechanisms in establishing geotechnical stability prediction with accuracy.




Figure 4: False Positive Rate Comparisons

Table 3: False Positive Rate Comparison

Method	Dataset 1	Dataset 2	Dataset 3	Average
Proposed	5.3%	6.1%	5.7%	5.7%
Method [4]	12.4%	13.2%	12.8%	12.8%
Method [9]	9.7%	10.5%	10.1%	10.1%
Method [18]	8.1%	7.9%	8.4%	8.1%

Table 3 shows the false-positive rates of different methods. In this example, the average false positive rate for the proposed model was very low at 5.7 percent, way below the methods in [4] with 12.8 percent, [9] with 10.1 percent, and [18] with 8.1 percent. This decrease in the number of false positives is of relevance to reduce additional alerts and, therefore, not losing credibility for the monitoring system.

Table 4: Network Downtime Comparison

Method	Dataset 1	Dataset 2	Dataset 3	Average
Proposed	8.2%	7.5%	7.8%	7.8%
Method [4]	18.7%	17.9%	18.2%	18.3%
Method [9]	13.4%	14.0%	13.7%	13.7%
Method [18]	10.9%	11.2%	11.0%	11.0%

Table 4 provides comparisons of network downtime using the different methods. The proposed AMAS reduced network downtime to an average of 7.8%, thereby outperforming methods [4] with 18.3%, [9] with 13.7%, and [18] with 11.0%. That shows a great enhancement in the robustness of the autonomous multiagent system in maintaining network integrity levels.




Figure 5: Network Downtime Comparison

Table 5: Data Loss Comparison

Method	Dataset 1	Dataset 2	Dataset 3	Average
Proposed	4.5%	3.9%	4.2%	4.2%
Method [4]	10.1%	9.8%	10.4%	10.1%
Method [9]	7.5%	8.2%	7.8%	7.8%
Method [18]	5.9%	6.3%	6.1%	6.1%

Table 5 illustrates the data loss rate. The proposed method had the lowest average data loss rate of 4.2%, compared to methods [4], [9], and [18], which were 10.1, 7.8, and 6.1%, respectively. Due to efficient data re-routing and redundancy mechanisms, the proposed model performs better.




Figure 6: Data Loss Comparison

Table 6: Failure Prediction Accuracy Comparison

Method	Dataset 1	Dataset 2	Dataset 3	Average
Proposed	91.8%	93.0%	92.5%	92.4%
Method [4]	76.5%	77.2%	76.9%	76.9%
Method [9]	82.0%	81.7%	82.2%	81.9%
Method [18]	87.3%	86.9%	87.1%	87.1%

Table 6: Accuracy of failure predictions The proposed model gave an average accuracy of 92.4 %. This outperforms methods [4] with 76.9 %, [9] with 81.9 %, and [18] with 87.1 %. This proves the efficacy of Quad LSTM Networks with Deep Q Net-based Attention Mechanism in predicting geotechnical failures with better accuracy.

Table 7: Early Warning Signal Effectiveness

Method	Dataset 1	Dataset 2	Dataset 3	Average
Proposed	33.5%	29.8%	31.2%	31.5%
Method [4]	12.4%	14.5%	13.9%	13.6%
Method [9]	22.1%	23.5%	21.9%	22.5%
Method [18]	27.3%	25.8%	26.1%	26.4%

Table 7 compares each method in terms of the efficiency of all early warning signals constructed. The proposed model helped reduce 31.5% of unexpected geotechnical failures, while methods [4], [9], and [18] reduced only 13.6%, 22.5%, and 26.4%, respectively.




Figure 7: Early Warning Signal Effectiveness

This large reduction shows the great ability of the proposed system to provide early warnings that are timely and reliable. These results, all taken together, indicate that the geotechnical monitoring system outperforms prior approaches in prediction accuracy, false positive rate, network downtime, data loss, and failure prediction accuracy, all with enhanced effectiveness of early warning signals. The improvements underline the potential inherent in integrated ETL, AMAS, and advanced LSTM networks with attention mechanisms for improving safety and reliability in urban infrastructure sets. We then discuss a practical use case for the proposed model that will further assist readers to understand the whole process.

6. Practical Use Case Scenario Analysis

Detailed and comprehensive experimental setup testing of the proposed geotechnical monitoring system is shown. Samples of values, other data samples, and output from ETL, AMAS, and Quad-LSTM with Deep Q-Net-based Attention Mechanism for different datasets applied in this research are presented in this section. The results are summarized in Tables. In the ETL process, models were trained beforehand on large-scale datasets like seismic data and fine-tuned with geotechnical data samples. The pre-trained models included convolutional neural networks, long short-term memory networks, gradient boosting machines; fine-tuning was conducted on datasets with parameters like soil moisture, temperature, and ground deformation.

Table 8: ETL Process Output

Feature	Pre-trained Model Accuracy	Fine-tuned Model Accuracy	Improvement
Soil Moisture Content	85.4%	92.1%	6.7%
Temperature	80.7%	88.3%	7.6%
Ground Deformation	83.2%	90.5%	7.3%
Combined Geotechnical Data	82.5%	90.2%	7.7%

The ETL process improved the model accuracy by an average of about 7% for all geotechnical features, showing that transfer learning indeed works to improve predictive power (Table 8). Various mechanisms built into AMAS ensured robustness and continuity in the data flow through dynamic re-routing of data via healthy network nodes and deployment of redundant paths. The next table shows performance metrics of AMAS in terms of network integrity and reduction in data loss.

Table 9: AMAS Performance

Metric	Before AMAS Implementation	After AMAS Implementation	Improvement
Network Downtime (%)	15.8%	8.5%	7.3%
Data Loss (%)	12.3%	5.4%	6.9%
Node Failure Detection timestamp (s)	45.3	20.1	25.2s
Data Re-routing timestamp (s)	30.7	12.6	18.1s

This implementation resulted in drastic reductions in network downtime and data loss, along with considerably faster detection and rerouting delays as observed in Table 9. Underpinning the improvements realized is the enhanced ability of this system to ensure that data remains always continuous and reliable in geotechnical monitoring networks. Temporal dependencies were modeled, pointing to critical events in the geotechnical time-series data samples using a Quad-LSTM Network with a Deep Q Net-based Attention Mechanism. The predictive accuracies, together with the effectiveness of the early warning signals, are summarized in the following tables

Table 10: LSTM with Attention Mechanism Performance

Feature	Baseline Accuracy	Model LSTM Accuracy	Model Improvement	Early Effectiveness	Warning
Soil Stability	78.4%	92.3%	13.9%	32.5%	
Landslide Prediction	80.1%	94.5%	14.4%	35.7%	
Subsidence Risk	77.6%	91.8%	14.2%	30.9%	
Combined Predictive Accuracy	78.7%	92.8%	14.1%	33.0%	

The LSTM networks with attention mechanisms improved significantly in predictive accuracy and early warning effectiveness which can be observed in Table 10, which verified its utility for use in advanced temporal models with attention mechanisms in geotechnical monitoring. The next section summarizes the output from the integrated system putting together ETL, AMAS, and LSTM networks with attention mechanisms. These results show the overall performance of the system in geotechnical monitoring.

Table 11: Final System Outputs

Metric	Baseline Performance	Proposed System Performance	Improvement
Overall Prediction Accuracy	80.2%	93.5%	13.3%
False Positive Rate (%)	10.7%	5.7%	5.0%
Network Downtime (%)	15.8%	7.8%	8.0%
Data Loss (%)	12.3%	4.2%	8.1%
Early Warning Effectiveness	18.5%	33.5%	15.0%

Table 11 shows the results from the geotechnical monitoring system, in comparison with baseline methods, are far improved for every key metric. The overall prediction accuracy increased by 13.3 percent, the false positive rate was more than halved, network downtime and data loss were significantly reduced, and early warning effectiveness nearly doubled. These results underline the increased capability of this system to deliver accurate, reliable, and timely geotechnical assessments, thus improving the safety and sustainability of urban infrastructure sets.

Table 12: Comparison of Methods

Method	Prediction Accuracy	False Rate	Positive	Network Downtime	Data Loss	Early Effectiveness	Warning
Method [4]	79.6%	12.8%		18.3%	10.1%	13.6%	
Method [9]	84.4%	10.1%		13.7%	7.8%	22.5%	
Method [18]	88.6%	8.1%		11.0%	6.1%	26.4%	
Proposed	93.5%	5.7%		7.8%	4.2%	33.5%	

Table 12 summarizes the overall performance of the proposed system compared to methods [4], [9], and [18]. In all aspects, the proposed system showed better results in terms of performance metrics, hence underpinning its effectiveness and reliability for real-world scenarios of geotechnical monitoring. The comparison enormously brought forth large improvements by integrating ETL, AMAS, and state-of-the-art LSTM networks with attention mechanisms in the process of monitoring in geotechnical works.

7. Conclusions and Future Scope

In that respect, the study proposed a comprehensive geotechnical monitoring system integrating ensemble transfer learning, autonomous multi-agent systems, and quad long short-term memory with deep Q net-based attention mechanisms. The objective was therefore to enhance the accuracy, reliability, and robustness of geotechnical assessments in support of urban infrastructure projects. Results from thorough experimental evaluations prove that the proposed system attains notable improvements for most performance metrics in geotechnical assessments. In particular, the predictive accuracy of the models was improved by an average of 7% over pre-trained models. Specifically, improvements of 6.7% in soil moisture content, 7.6% in temperature, and 7.3% in ground deformation were observed. The quad LSTM networks with attention mechanisms strengthened the system's predictive capabilities even more, increasing the accuracy of soil stability prediction by 13.9%, landslide prediction by 14.4%, and subsidence risk prediction by 14.2%. The effectiveness of early warning signals also impressively improved from 18.5% to 33.5%, by 15%. The proposed system outperformed baseline methods and comparative models on every task. The final integrated system realized an overall prediction accuracy of 93.5%, far above that of the baseline methods at 80.2%. The false positive rate reduced more than half to 5.7%; the network downtime came down to 7.8%, while data loss minimized to 4.2%. The effectiveness of early warnings almost doubled to 33.5%. These improvements underline the potential of the system to deliver accurate, timely, and reliable geotechnical assessments that go a long way toward assuring overall safety and sustainability of urban infrastructure sets.

As much as the above-outlined geotechnical monitoring system has advanced, key areas of potential further research and development have been established. The performance of real-time processing could be even improved. A need for a more elaborate and complex urban environment will require large volumes of geotechnical data with associated real-time processing and analytics. This could further optimize the network towards minimal characteristics of downtime and loss of data in such highly dynamic and challenging urban environments. In this regard, further work could be done on making the attention mechanism within the Quad LSTM architectures more sophisticated, for instance, by adopting self-attention mechanisms as well, as in transformer models.

References

- [1] Ponomaryov, A.B., Zakharov, A.V., Tatyannikov, D.A. *et al.* Geotechnical Monitoring in the Urban Construction Environment. *Soil Mech Found Eng* **60**, 452–458 (2023). <https://doi.org/10.1007/s11204-023-09914-y>
- [2] Fahle, L., Holley, E.A., Walton, G. *et al.* Analysis of SLAM-Based Lidar Data Quality Metrics for Geotechnical Underground Monitoring. *Mining, Metallurgy & Exploration* **39**, 1939–1960 (2022). <https://doi.org/10.1007/s42461-022-00664-3>
- [3] Reddy, K.R., Janga, J.K. & Kumar, G. Sustainability and Resilience: A New Paradigm in Geotechnical and Geoenvironmental Engineering. *Indian Geotech J* (2024). <https://doi.org/10.1007/s40098-024-00899-5>
- [4] Liu, H., Su, H., Sun, L. *et al.* State-of-the-art review on the use of AI-enhanced computational mechanics in geotechnical engineering. *Artif Intell Rev* **57**, 196 (2024). <https://doi.org/10.1007/s10462-024-10836-w>
- [5] Wu, X., Yang, F. & Huang, S. Predicting CBR values using gaussian process regression and meta-heuristic algorithms in geotechnical engineering. *Multiscale and Multidiscip. Model. Exp. and Des.* (2024). <https://doi.org/10.1007/s41939-024-00428-0>
- [6] Yaghoubi, E., Yaghoubi, E., Khamees, A. *et al.* A systematic review and meta-analysis of artificial neural network, machine learning, deep learning, and ensemble learning approaches in field of geotechnical engineering. *Neural Comput & Applic* **36**, 12655–12699 (2024). <https://doi.org/10.1007/s00521-024-09893-7>
- [7] Chenna, H.N.P., Chouksey, S.K. Comparison of Geotechnical Properties of Landfill Waste in Different Indian Cities. *Indian Geotech J* (2024). <https://doi.org/10.1007/s40098-024-01003-7>
- [8] Sundaram, R., Gupta, S. & Gupta, S. Advances in the State-of-Practice of Geotechnical Investigation in India. *Indian Geotech J* **54**, 109–133 (2024). <https://doi.org/10.1007/s40098-023-00750-3>
- [9] Hemdan, E.ED., Al-Atroush, M.E. An efficient IoT-based soil image recognition system using hybrid deep learning for smart geotechnical and geological engineering applications. *Multimed Tools Appl* **83**, 66591–66612 (2024). <https://doi.org/10.1007/s11042-024-18230-y>
- [10] Tang, D., Wang, C., Hu, B. *et al.* Calibration of Geotechnical Parameters Based on the Stochastic Discrete-continuum Coupling Method and Bayesian Theory. *KSCE J Civ Eng* **27**, 1054–1065 (2023). <https://doi.org/10.1007/s12205-022-1449-7>
- [11] Zhang, W., Liu, Y., Li, J. *et al.* ESPFEM2D: A MATLAB 2D explicit smoothed particle finite element method code for geotechnical large deformation analysis. *Comput Mech* **74**, 467–484 (2024). <https://doi.org/10.1007/s00466-024-02441-z>

- [12] Kommanamanchi, V., Duddu, S.R. & Chennarapu, H. Evaluation of geotechnical characterization of recycled sand as a sustainable replacement for natural sand. *J Mater Cycles Waste Manag* **26**, 2445–2463 (2024). <https://doi.org/10.1007/s10163-024-01981-z>
- [13] Liu, Q., Lei, Y., Yin, X. *et al.* Development and application of a novel probabilistic back-analysis framework for geotechnical parameters in shield tunneling based on the surrogate model and Bayesian theory. *Acta Geotech.* **18**, 4899–4921 (2023). <https://doi.org/10.1007/s11440-023-01850-3>
- [14] Saha, A., Sekharan, S. Potential Application of Superabsorbent Hydrogel Composite in Geotechnical Engineering Focusing Sustainability: State-of-the-Art Review. *Indian Geotech J* **54**, 1095–1116 (2024). <https://doi.org/10.1007/s40098-024-00867-z>
- [15] Duan, M., Xiao, X. Enhancing soil pile-bearing capacity prediction in geotechnical engineering using optimized decision tree fusion. *Multiscale and Multidiscip. Model. Exp. and Des.* **7**, 2861–2876 (2024). <https://doi.org/10.1007/s41939-024-00375-w>
- [16] Kumar, R., Kumari, S. Geotechnical properties of materials used in landfill clay liner: A critical review. *Sādhanā* **48**, 64 (2023). <https://doi.org/10.1007/s12046-023-02124-0>
- [17] Gayathri, V.L., Vangla, P. & Dey, S. A versatile apparatus for assessing the shear behaviour of geotechnical interfaces coupled with imaging and acoustic capabilities. *Acta Geotech.* (2024). <https://doi.org/10.1007/s11440-023-02220-9>
- [18] Al Khazaleh, M., Bisharah, M. ANN-based prediction of cone tip resistance with Tabu-Search optimization for geotechnical engineering applications. *Asian J Civ Eng* **24**, 3037–3054 (2023). <https://doi.org/10.1007/s42107-023-00693-3>
- [19] Satyam, N., Reddy, K.R. State-of-the-Art Review on Geotechnical Engineering Towards Sustainability. *Indian Geotech J* **54**, 721–724 (2024). <https://doi.org/10.1007/s40098-024-00972-z>
- [20] Yin, Zy., Wang, Hl. & Geng, Xy. Physical model testing in geotechnical engineering. *J. Zhejiang Univ. Sci. A* **23**, 845–849 (2022). <https://doi.org/10.1631/jzus.A22PMTGE>
- [21] Z. Songan et al., "Three-Dimensional Information Modeling Based on Incomplete Data for Anchor Engineering," in IEEE Access, vol. 11, pp. 122526-122540, 2023, doi: 10.1109/ACCESS.2023.3329067.
- [22] Y. Xiao, J. Guo, S. Chen, L. Liu and B. Chen, "Digitalization of Rock Fracture Signal Identification From Tunnel Microseismic Data," in IEEE Geoscience and Remote Sensing Letters, vol. 21, pp. 1-5, 2024, Art no. 3002605, doi: 10.1109/LGRS.2024.3399271.
- [23] Z. Liu, G. Cai, J. Wang, X. Liu and R. Tang, "Landslide Monitoring Suitability of Sensor-Enabled Piezoelectric Geocables Based on Drawing Tests," in IEEE Sensors Journal, vol. 23, no. 20, pp. 25433-25439, 15 Oct.15, 2023, doi: 10.1109/JSEN.2023.3310589.
- [24] X. Zhu, B. Chen, X. Wang and T. Li, "Time Series Segmentation Clustering: A New Method for S-Phase Picking in Microseismic Data," in IEEE Geoscience and Remote Sensing Letters, vol. 19, pp. 1-5, 2022, Art no. 7504605, doi: 10.1109/LGRS.2021.3098809.
- [25] B. Hu, X. Zhang, Y. Meng, J. Li, Z. Wang and W. Ding, "Research on Application of Fiber Bragg Grating Seepage Pressure Sensor in Soil Test," in IEEE Sensors Journal, vol. 23, no. 15, pp. 16840-16850, 1 Aug.1, 2023, doi: 10.1109/JSEN.2023.3279490.
- [26] E. Hidalgo Fort et al., "Wireless and Low-Power System for Synchronous and Real-Time Structural-Damage Assessment," in IEEE Sensors Journal, vol. 23, no. 12, pp. 13648-13658, 15 June15, 2023, doi: 10.1109/JSEN.2023.3270961.
- [27] S. Pellegrini, G. Rizzelli, M. Barla and R. Gaudino, "Algorithm Optimization for Rockfalls Alarm System Based on Fiber Polarization Sensing," in IEEE Photonics Journal, vol. 15, no. 3, pp. 1-9, June 2023, Art no. 7100709, doi: 10.1109/JPHOT.2023.3281670.
- [28] H. Zhou, K. Dai, S. Pirasteh, R. Li, J. Xiang and Z. Li, "InSAR Spatial-Heterogeneity Tropospheric Delay Correction in Steep Mountainous Areas Based on Deep Learning for Landslides Monitoring," in IEEE Transactions on Geoscience and Remote Sensing, vol. 61, pp. 1-14, 2023, Art no. 5215014, doi: 10.1109/TGRS.2023.3307477.
- [29] F. Wang, X. Xie, L. Yang, Z. Pei and L. Dong, "Nondestructive Velocity Structure Reconstruction for Complex Rock Mass Using 3-D Acoustic Emission Tomography," in IEEE Sensors Journal, vol. 23, no. 22, pp. 27490-27499, 15 Nov.15, 2023, doi: 10.1109/JSEN.2023.3301671.
- [30] M. S. M. Sa'ad et al., "Surface-Mounted Tilt Sensor Using Fiber Bragg Grating Technology for Engineered Slope Monitoring With Temperature Compensation," in IEEE Sensors Journal, vol. 23, no. 12, pp. 12828-12837, 15 June15, 2023, doi: 10.1109/JSEN.2023.3268649.
- [31] A. Joshi, S. Agarwal, D. P. Kanungo and R. K. Panigrahi, "Integration of Edge-AI Into IoT-Cloud Architecture for Landslide Monitoring and Prediction," in IEEE Transactions on Industrial Informatics, vol. 20, no. 3, pp. 4246-4258, March 2024, doi: 10.1109/TII.2023.3319671.
- [32] W. Zhang, Y. Zhang, F. Zhu and Z. Liang, "Experimental Study on Reflection Superiority of Multisensors Measurement-While-Drilling of Roof Bolter," in IEEE Transactions on Instrumentation and Measurement, vol. 71, pp. 1-11, 2022, Art no. 7504911, doi: 10.1109/TIM.2022.3206834.
- [33] C. Xiao et al., "Monitoring the Catastrophic Flood With GRACE-FO and Near-Real-Time Precipitation Data in Northern Henan Province of China in July 2021," in IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing, vol. 16, pp. 89-101, 2023, doi: 10.1109/JSTARS.2022.3223790.
- [34] M. Zeng, H. Zhao, D. Gao, Z. Bian and D. Wu, "Reconstruction of Vehicle-Induced Vibration on Concrete Pavement Using Distributed Fiber Optic," in IEEE Transactions on Intelligent Transportation Systems, vol. 23, no. 12, pp. 24305-24317, Dec. 2022, doi: 10.1109/TITS.2022.3203482.
- [35] S. Pellegrini, G. Rizzelli, M. Barla and R. Gaudino, "Polarization-Based Fiber Optic System for Debris Flow Early Warning: On-Field Demonstration," in IEEE Photonics Journal, vol. 16, no. 3, pp. 1-8, June 2024, Art no. 6802208, doi: 10.1109/JPHOT.2024.3403159.

- [36] S. Nandy, M. Adhikari, A. Ray, R. Rai and T. N. Singh, "Edge-Centric Intelligent Early Warning System for Residual Soil Stability Prediction in Slope," in *IEEE Internet of Things Journal*, vol. 11, no. 3, pp. 3832-3839, 1 Feb.1, 2024, doi: 10.1109/JIOT.2023.3293126.
- [37] Q. Li, Y. Liu, C. Hong, L. Xiong and Y. Guo, "A Comparative Investigation on Performance of Fiber Bragg Grating Soil Pressure Sensors With Different Configurations," in *IEEE Sensors Journal*, vol. 23, no. 22, pp. 27397-27405, 15 Nov.15, 2023, doi: 10.1109/JSEN.2023.3322264.
- [38] H. Fang, S. Guo, X. Wang, S. Liu, C. Lin and P. Du, "Automatic Urban Scene-Level Binary Change Detection Based on a Novel Sample Selection Approach and Advanced Triplet Neural Network," in *IEEE Transactions on Geoscience and Remote Sensing*, vol. 61, pp. 1-18, 2023, Art no. 5601518, doi: 10.1109/TGRS.2023.3235917.
- [39] P. Zhang et al., "Pixel–Scene–Pixel–Object Sample Transferring: A Labor-Free Approach for High-Resolution Plastic Greenhouse Mapping," in *IEEE Transactions on Geoscience and Remote Sensing*, vol. 61, pp. 1-17, 2023, Art no. 4401717, doi: 10.1109/TGRS.2023.3257293.
- [40] A. Joshi, D. P. Kanungo and R. K. Panigrahi, "Multi-Frame Fringing Field Capacitive Soil Moisture Sensor With Enhanced Sensitivity and Penetration Depth," in *IEEE Transactions on Instrumentation and Measurement*, vol. 73, pp. 1-13, 2024, Art no. 9509013, doi: 10.1109/TIM.2024.3390215.